

NORMACLAMP® – Hose Clamps

Variants



NORMACLAMP® HD

HD clamps are suitable for special areas of application where high tightening torques and high contact pressures are required, for example, for fastening steel reinforced silicon, plastic and rubber hoses.

The extended bridge prevents the hose from protruding and being damaged.

The NORMACLAMP® HD clamp is an add-on type to our range of worm drive hose clips and therefore only available in 16 mm band width and W4 material quality.

Features

- Only 16 mm band width
- Only W4 material

NORMACLAMP® – Hose Clamps

Survey of sizes, band widths & materials NORMACLAMP® TORRO® HD

Band width (mm)	Description	Clamping Range		Packaging		B	h	L	s	W4
		in mm	in Inches	PU	IC					
16	HD 25-45/16 C8 W4	25-45	1-13/4	50	250	23.0	13.0	37.0	0.7	X
16	HD 32-54/16 C8 W4	32-54	1 1/4-2 1/8	50	250	23.0	13.0	37.0	0.7	X
16	HD 45-67/16 C8 W4	45-67	1 3/4-2 5/8	50	250	23.0	13.0	37.0	0.7	X
16	HD 57-79/16 C8 W4	57-79	2 1/4-3 1/8	50	250	23.0	13.0	37.0	0.7	X
16	HD 70-92/16 C8 W4	70-92	2 3/4-3 5/8	25	250	23.0	13.0	37.0	0.7	X
16	HD 83-105/16 C8 W4	83-105	3 1/4-4 1/8	10	100	23.0	13.0	37.0	0.7	X
16	HD 95-118/16 C8 W4	95-118	3 3/4-4 5/8	10	100	23.0	13.0	37.0	0.7	X
16	HD 108-130/16 C8 W4	108-130	4 1/4-5 1/8	10	100	23.0	13.0	37.0	0.7	X
16	HD 121-143/16 C8 W4	121-143	4 3/4-5 5/8	10	100	23.0	13.0	37.0	0.7	X
16	HD 133-156/16 C8 W4	133-156	5 1/4-6 1/8	10	100	23.0	13.0	37.0	0.7	X
16	HD 146-168/16 C8 W4	146-168	5 3/4-6 5/8	10	100	23.0	13.0	37.0	0.7	X
16	HD 159-181/16 C8 W4	159-181	6 1/4-7 1/8	10	50	23.0	13.0	37.0	0.7	X
16	HD 172-194/16 C8 W4	172-194	6 3/4-7 5/8	10	50	23.0	13.0	37.0	0.7	X
16	HD 184-206/16 C8 W4	184-206	7 1/4-8 1/8	10	50	23.0	13.0	37.0	0.7	X
16	HD 197-219/16 C8 W4	197-219	7 3/4-8 5/8	10	50	23.0	13.0	37.0	0.7	X
16	HD 210-232/16 C8 W4	210-232	8 1/4-9 1/8	10	50	23.0	13.0	37.0	0.7	X

Enquiries/ordering:

When making enquiries or placing an order please indicate as follows:

Further sizes on request

- B = total width in mm (housing)
- h = total height in mm (screw and housing)
- IC = industrial carton
- L = total length in mm (screw and housing)
- PU = packaging unit
- s = band thickness in mm (clamp band)

Example	1. Type	2. Clamping Range	3. Band width	4. Screw	5. Material
	TORRO® with spring insert	35-50/	9	C7	W4